



PEGASUS

QUALITY SPEAKS FOR ITSELF®



SCAN TO VIEW ALL TIRE LINES



TOUR AS

- **Wide circumferential grooves and high-density siping improves traction in wet and light snow conditions**
- **Reinforced large shoulder block area provides confident cornering capability and controlled handling**
- **Optimized pitch sequence reduces tread pattern noise for a quiet ride**
- **50,000-mile treadwear warranty**
- **1-Year Road Hazard Protection Plan**

TIRE SIZE	LI	OD	SW	TD	LOAD
185/60R15 XL	88H	23.7	7.4	9	1235
185/65R15	88H	24.5	7.4	9	1235
195/60R15	88V	24.2	7.9	10	1235
195/65R15	91V	25	7.9	10	1356
205/60R15	91V	24.7	8.2	10	1356
205/65R15	94H	25.5	8.2	10	1477
205/70R15	96H	26.3	8.2	10	1565
215/70R15	98T	26.9	8.7	10	1653
205/55R16	91V	24.9	8.4	10	1356
205/60R16	92V	25.7	8.2	10	1389
205/65R16	95H	26.5	8.2	10	1521
215/55ZR16 XL	97W	25.3	8.9	10	1609
215/60R16	95H	26.1	8.7	10	1521
215/65R16	98H	27	8.7	10	1653
225/60R16	98V	26.6	9.0	10	1653
225/65R16	100H	27.5	9	10	1764
215/60R17	96V	27.2	8.7	10	1565
215/65R17	99H	28	8.7	10	1709
225/60R17	99V	27.6	9	10	1709
225/65R17	102H	28.5	9	10	1874
235/65R17	104H	29.1	9.5	10	1984
225/60R18	100V	28.6	9	10	1764
235/60R18 XL	107V	29.1	9.5	10	2149





HPX SPORT AS



TIRE SIZE	LI	OD	SW	TD	LOAD
235/55ZR17 XL	103W	27.2	9.7	10	1929
205/45ZR17 XL	88W	24.3	8.1	9	1235
205/50ZR17 XL	93W	25.1	8.4	10	1433
215/50ZR17 XL	95W	25.5	8.9	10	1521
215/55ZR17 XL	98W	26.3	8.9	10	1653
225/50ZR17 XL	98W	25.9	9.2	10	1653
225/45ZR17 XL	94W	25	8.9	9	1477
225/55ZR17 XL	101W	26.8	9.2	10	1819
235/45ZR17 XL	97W	25.4	9.3	9	1609
245/40ZR17 XL	95W	24.7	9.8	9	1521
235/50ZR17 XL	100W	26.3	9.7	10	1764
215/45ZR17 XL	91W	24.7	8.4	9	1356
235/45ZR18 XL	98W	25.1	9.1	9	1389
245/45ZR18 XL	100W	26.7	9.6	9	1764
225/45ZR18 XL	95W	25.9	8.9	9	1521
225/40ZR18 XL	92W	25.1	9.1	9	1389
235/40ZR18 XL	95W	25.4	9.5	9	1521
225/50ZR18 XL	99W	26.9	9.2	10	1709
235/50ZR18 XL	101W	27.3	9.7	10	1819
255/35ZR18 XL	94W	25	10.2	9	1477
235/55ZR18 XL	104W	28.2	9.7	10	1984
245/40ZR18 XL	97W	25.7	9.8	9	1609
225/40ZR19 XL	93W	26.1	9.1	9	1433
225/55ZR19 XL	103W	28.8	9.2	10	1929
235/35ZR19 XL	91W	25.5	9.5	9	1356
235/40ZR19 XL	96W	26.4	9.5	9	1565
235/50ZR19 XL	103W	28.3	9.7	10	1929
235/55ZR19 XL	105W	29.2	9.7	10	2039
245/40ZR19 XL	98W	26.7	9.8	9	1653
245/45ZR19 XL	102W	27.7	9.6	9	1874
255/35ZR19 XL	96W	26	10.2	9	1565
255/40ZR19 XL	100W	27.1	10.2	9	1764
255/45ZR19 XL	104W	28.1	10	9	1984

- **Asymmetric tread design for enhanced handling and braking performance**
- **Innovative tread pattern, with additional tread blocks, minimizes noise and absorbs road impact, providing a more comfortable driving experience.**
- **Optimized inside tread pattern enhances wet, dry, and winter traction**
- **Four large circumferential grooves provide improved wet traction and resistance to hydroplaning**
- **50,000-mile limited treadwear warranty**
- **1-Year Road Hazard Protection Plan**

<i>TIRE SIZE</i>	<i>LI</i>	<i>OD</i>	<i>SW</i>	<i>TD</i>	<i>LOAD</i>
255/55ZR19 XL	111W	30	10.4	10	2403
225/35ZR20 XL	90W	26.2	9.1	9	1323
225/30ZR20 XL	85W	25.4	9.1	9	1135
235/35ZR20 XL	92W	26.5	9.5	9	1389
235/55ZR20 XL	105W	30.2	9.7	10	2039
245/35ZR20 XL	95W	26.8	9.8	9	1521
245/40ZR20 XL	99W	27.7	9.8	9	1709
245/45ZR20 XL	103W	28.7	9.6	9	1929
245/50ZR20 XL	105W	29.7	10	10	2039
255/35ZR20 XL	97W	27	10.2	9	1609
255/45ZR20 XL	105W	29.1	10	9	2039
255/50ZR20 XL	109W	30.1	10.4	10	2271
265/50ZR20 XL	111W	30.5	10.9	10	2403
275/30ZR20 XL	97W	36.5	10.9	9	1609
275/35ZR20 XL	102W	27.6	10.9	9	1874
275/40ZR20 XL	106W	28.7	10.9	9	2094
315/35ZR20 XL	110W	28.7	12.6	9	2337
235/30ZR22 XL	90W	27.6	9.5	9	1323
245/30ZR22 XL	92W	27.8	9.8	9	1389
255/30ZR22 XL	95Y	28.1	10.2	9	1521
265/30ZR22 XL	97W	28.3	10.7	9	1609
265/35ZR22 XL	102W	39.3	10.7	9	1874
265/40ZR22 XL	106W	30.4	10.7	9	1609
285/35ZR22 XL	106W	29.9	11.4	9	2094
285/45ZR22 XL	114W	32.1	11.2	9	2601
305/40R22 XL	114V	31.6	12.3	9	2601
305/45R22 XL	118V	32.8	11.9	9	2910
255/30ZR24 XL	97W	30.1	10.2	9	1609
275/25ZR24 XL	96W	29.5	11.1	9	1565
295/35ZR24 XL	110W	32.1	11.9	9	2337
305/35R24 XL	112V	32.4	12.3	9	2469
305/30ZR26 XL	109W	33.2	12.3	9	2271



HTX AS



<i>TIRE SIZE</i>	<i>LI</i>	<i>OD</i>	<i>SW</i>	<i>TD</i>	<i>LOAD</i>
215/70R16	100H	27.9	8.7	10	1764
235/70R16	106T	29	9.5	10	2094
245/70R16 XL	111T	29.5	9.8	10	2403
255/70R16	111H	30.1	10.2	11	2403
265/70R16	112T	30.6	10.7	11	2469
225/65R17	102H	28.5	9	10	1874
235/65R17	104T	29.1	9.5	10	1984
245/65R17	107H	29.5	9.8	10	2149
245/70R17	110H	30.6	9.8	10	2337
265/70R17	115T	31.7	10.7	11	2679
235/55R18 XL	104V	28.2	9.7	10	1984
235/65R18 XL	110H	30	9.5	10	2337
245/60R18	105H	29.6	9.8	10	2039
255/55R18 XL	109W	29	10.4	11	2271
255/65R18	111H	31.1	10.2	11	2403
265/60R18	110H	30.5	10.7	11	2337
265/65R18	114H	31.5	10.7	11	2601
265/70R18	116H	32.6	10.7	11	2756
275/65R18	116H	32.1	11	11	2756
235/60R18 XL	107V	29.1	9.5	10	2149
275/55R20 XL	117H	32	11.2	11	2833
275/60R20	115T	33	11	11	2679
LT215/85R16/10	115/112S	30.4	8.5	12	2680/2470
LT235/85R16/10	120/116S	31.7	9.3	12	3085/2755
LT225/75R16/10	115/112S	29.3	8.8	12	2680/2470
LT245/75R16/10	120/116S	30.5	9.8	12	3085/2755
LT265/75R16/10	123/120S	31.7	10.5	13	3415/3085
LT235/80R17/10	120/117S	31.8	9.3	12	3085/2835
LT245/75R17/10	121/118S	31.5	9.8	12	3195/2910
LT245/70R17/10	119/116S	30.6	9.8	12	3000/2755
LT265/70R17/10	123/120S	31.7	10.7	13	3415/3085
LT275/70R18/10	125/122S	33.2	11	13	3640/3305



- **Tread design reduces noise to ensure a smooth quiet ride on all road surfaces.**
- **Computer optimized footprint for excellent wear and handling under multiple road conditions**
- **Four extra-wide grooves and heavy tread block siping channel water to give you the all-weather traction you need to drive with confidence.**
- **Four large circumferential grooves provide improved wet traction and resistance to hydroplaning**
- **50,000-mile limited treadwear warranty**
- **LT sizes: 40,000-mile limited treadwear warranty**
- **1-Year Road Hazard Protection Plan**



ATX 4S



Tire Size	LI	OD	SW	TD	Load
245/70R16	107T	29.5	9.8	12	2150
265/70R16	112T	30.6	10.7	12	2470
245/75R16	111T	30.5	9.8	12	2405
265/70R17	115T	31.7	10.7	12	2680
245/65R17	107T	29.5	9.8	12	2150
275/65R18	116T	32.1	11	12	2755
265/60R18 XL	114T	30.5	10.7	12	2600
275/60R20 XL	116T	33	11	12	2755
275/55R20 XL	117T	31.9	11.2	12	2835
265/50R20 XL	111T	30.5	10.9	12	2405
LT235/75R15/6	104/101S	28.9	9.3	14	1985/1820
LT235/85R16/10	120/116S	31.7	9.3	14	3085/2755
LT225/75R16/10	115/112S	29.3	8.8	14	2680/2470
LT245/75R16/10	120/116S	30.5	9.8	14	3085/2755
LT265/75R16/10	123/120S	31.7	10.5	14	3415/3085
LT285/75R16/10	126/123S	32.8	11.3	14	3750/3415
LT315/75R16/10	127/124S	34.6	12.3	15	3860/3525
LT265/70R16/10	123/120S	31.7	10.5	14	3415/3085
LT305/70R16/10	124/121S	32.8	12.2	15	3525/3195
LT235/80R17/10	120/117S	31.8	9.3	14	3085/2835
LT245/75R17/10	121/118S	31.5	9.8	14	3195/2910
LT265/70R17/10	121/118S	30.6	10.7	14	3195/2910
LT285/70R17/10	126/123S	32.8	11.5	14	3750/3415
LT265/70R18/10	124/121S	32.6	10.7	14	3525/3195
LT275/70R18/10	125/122S	33.2	11	14	3640/3305
LT275/65R18/10	123/120S	32.1	11	14	3415/3085
LT285/65R18/10	125/122S	32.6	11.5	14	3640/3305
LT275/65R20/10	126/123S	34.1	11	14	3750/3415
LT265/60R20/10	121/118S	35.5	10.7	14	3195/2910
LT275/60R20/10	123/120S	33	11	14	3415/3085
LT285/55R20/10	122/119T	32.4	11.7	14	3305/3000
LT275/55R20/10	120/117S	31.9	11.2	14	3085/2835
LT305/55R20/10	121/118S	33.2	12.4	15	3195/2910
31X10.50R15LT/6	109S	30.5	10.6	14	2270
33x12.50R17LT/10	120R	32.5	12.5	15	3085
35x12.50R17LT/10	125R	34.5	12.5	15	3640
33X12.50R18LT/10	118R	32.5	12.5	15	2910
35X12.50R18LT/10	123R	34.5	12.5	15	3415
33x12.50R20LT/12	119S	32.5	12.5	15	3000
35x12.50R20LT/12	125R	34.5	12.5	15	3640
<ul style="list-style-type: none"> 3 Peak Mountain Snowflake Certified (3PMS) ensures excellent performance in snow conditions Elaborate siping and enhanced tread design allows for superior water dispersion. Variable circumferential grooves and multi-pitch shoulder design reduce highway noise and minimize hydroplaning Four large circumferential grooves provide improved wet traction and resistance to hydroplaning 50,000-mile limited treadwear warranty LT sizes: 40,000-mile limited treadware warranty 1-Year Road Hazard Protection Plan 					



RTX





- **Optimized tread block sizes and shapes with multiple lateral grooves and angled channels provide excellent all terrain traction.**
- **Interlocking interior tread blocks provide stability and more even treadwear.**
- **Squared profile and staggered scalloped shoulder lugs with stone ejectors maximize traction while removing debris in the voids.**
- **Variable circumferential grooves and multi-pitch shoulder design reduces highway noise and minimize hydroplaning**
- **50,000-mile limited treadwear warranty**
- **LT sizes: 40,000-mile limited treadware warranty**

TIRE SIZE	LI	OD	SW	TD	LOAD
LT245/75R17/10	121/118Q	31.5	9.8	14	3195/2910
LT265/70R17/10	123/120Q	31.7	10.7	14	3415/3085
LT285/70R17/10	126/123Q	32.8	11.5	14	3750/3415
LT275/65R18/10	123/120Q	32.1	11	14	3415/3085
LT275/70R18/12	128/125Q	33.2	11	14	3970/3415
LT275/65R20/10	126/123R	34.1	11	14	3750/3415
LT285/65R20/10	127/124Q	34.6	11.5	14	3860/3525
LT265/60R20/10	121/118Q	32.5	10.7	14	3195/2910
LT275/55R20/10	120/117Q	31.9	11.2	14	3085/2835
LT285/55R20/10	122/119S	32.4	11.7	14	3305/3000
LT305/55R20/12	125/122S	33.2	12.4	14	3640/3305
33X12.50R17LT/10	120Q	32.5	12.5	17	3085
35X12.50R17LT/10	125Q	34.5	12.5	17	3640
37X12.50R17LT					
40X13.50R17LT					
33X12.50R18LT/12	122Q	32.5	12.5	17	3305
35X12.50R18LT/12	128Q	34.5	12.5	17	3970
33X11.50R20LT/10	118Q	32.5	11.4	17	2910
33X12.50R20LT/12	119Q	32.5	12.5	17	3000
35X12.50R20LT/12	125Q	34.5	12.5	17	3640
37X13.50R20LT/12	128Q	36.5	13.6	17	3970
33X12.50R22LT/12	114Q	32.5	12.5	17	2600
35X12.50R22LT/12	121Q	34.5	12.5	17	3195
37X13.50R22LT/12	128Q	36.5	13.6	17	3970
33X12.50R24LT/12	106Q	32.5	12.6	17	2095
35X12.50R24LT/12	116Q	34.5	12.4	17	2755
37X13.50R24LT/12	124Q	36.5	13.6	17	3525



MTX





- **Aggressive tread design featuring high void ratio and open shoulder design.**
- **High strength body plies with an aggressive self-cleaning tread and deep sipes to produce protection and maximum grip on uneven surfaces in all types of tough terrain**
- **Squared profile and staggered scalloped shoulder lugs with integrated stone ejectors maximize traction while removing debris in the voids**

<i>TIRE SIZE</i>	<i>LI</i>	<i>OD</i>	<i>SW</i>	<i>TD</i>	<i>LOAD</i>
LT235/85R16/10	120/116Q	31.7	9.3	16	3085/2755
LT245/75R16/10	120/116Q	30.5	9.8	16	3085/2755
LT265/75R16/10	123/120Q	31.7	10.5	17	3415/3085
LT285/75R16/10	126/123Q	32.8	11.3	17	3750/3415
LT315/75R16/10	127/124Q	34.6	12.3	17	3860/3525
LT265/70R17/10	123/120Q	31.7	10.7	17	3415/3085
LT285/70R17/10	126/123Q	32.8	11.5	17	3750/3415
LT275/70R18/10	125/122Q	33.2	11	17	3640/3305
LT275/65R18/10	123/120Q	32.1	11	17	3415/3085
LT285/65R18/10	125/122Q	32.6	11.5	17	3640/3305
LT275/55R20/10	120/117Q	31.9	11.2	17	3085/2835
LT285/55R20/10	122/119Q	32.4	11.7	17	3305/3000
31X10.5R15LT/6	109Q	30.5	11.2	17	2270
33X12.50R15LT/6	108Q	30.5	12.5	17	2205
33x12.50R17LT/10	120Q	32.5	12.5	19	3085
35x12.50R17LT/10	125Q	34.5	12.5	19	3640
33x12.50R18LT/12	122Q	32.5	12.5	19	3305
35x12.50R18LT/12	128Q	34.5	12.5	19	3970
33X12.50R20LT/12	119Q	32.5	12.5	19	3000
35X12.50R20LT/12	125Q	34.5	12.5	19	3640
37x13.50R20LT/12	128Q	36.5	13.6	19	3970
40X15.50R20LT/12	128Q	39.5	15.6	19	3970
33X12.50R22LT/12	114Q	32.5	12.5	19	2600
35X12.50R22LT/12	121Q	34.5	12.5	19	3195
37x13.50R22LT/12	128Q	36.5	13.6	19	3970
40X15.50R22LT/12	128Q	39.5	15.6	19	3970
33X12.50R24LT/12	106Q	32.5	12.6	19	2095
35x12.50R24LT/12	116Q	34.5	12.4	19	2755
37x13.50R24LT/12	124Q	36.5	13.6	19	3525



WARRANTY

100% FREE REPLACEMENT WARRANTY

American Pacific Industries, Inc (API) hereby warrants every new Pegasus LT/PCR tire for workmanship and material related conditions for the life of the original tread of a new tire less 2/32". The life of the original usable tread ends when the tire tread has worn down with only 2/32" remaining as measured in the fastest wearing groove, at which point the tire is considered to be fully worn out. API will refund the cost of a replacement Pegasus LT/PCR tire. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner. All Exclusions listed below void this 100% Free Replacement Warranty. Conditions and coverage are subject to change at any time and without notice.

- A) The Pegasus LT/PCR tire must be replaced with a comparable new Pegasus LT/PCR tire by an authorized Pegasus dealer. Copy of invoice will be required.
- B) 100% free replacement applies to new first quality tires. Blemished tires, retreads and road hazard tires are specifically excluded (see Road Hazard Warranty below),
- C) Adjustments on ride complaints or out of round tires are excluded from this warranty if they are worn past 2/32" from the original usable tread of the new tire.

FREE ROAD HAZARD WARRANTY

Every applicable Pegasus LT/PCR tire that has been irreparably damaged due to a normal road hazard condition (e.g. irreparable cut, puncture, snag, bruise, or impact break) within 1 year from the date of purchase OR less than 25% of the original tread depth will be replaced free of charge with an equivalent Pegasus LT/PCR tire. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner. To be eligible, you must present your original invoice showing date of purchase. All Exclusions listed below void this Road Hazard Warranty. Conditions and coverage are subject to change at any time and without notice. ALL ROAD HAZARD CLAIMS MUST BE SERVICED THROUGH YOUR AUTHORIZED PEGASUS DEALER.

Applicable Pegasus Lines with Road Hazard Warranty: Pegasus TOUR AS, HPX SPORT AS, ATX 4S, HTX AS

SATISFACTION ASSURED

All Pegasus LT/PCR tires are covered by the 30 Day "Satisfaction Assured" trial period. If, for any reason, other than an excluded condition listed in the respective tire's Standard Warranty, you are not satisfied with your new set of tires within 30 days of date of purchase - or the first 2/32nds of tread wear as measured in the fastest wearing groove (whichever comes first) - you may exchange all or any one of them for the same number of the same design or similar design API manufactured tires. Mounting and balancing are free of charge (excluding online orders). Owner pays all applicable taxes. If you wish to exchange for another set of API manufactured tires that have a higher cost, you must pay the upgrade from the original purchase price, including shipping and all applicable taxes. If you wish to exchange for another set of tires, which is at a lower cost, you will receive a credit for the difference in cost.

This Satisfaction Assurance guarantee only applies to the original new set of manufactured Pegasus LT/PCR tires purchased and not to the replacement tires under this guarantee.

Administration of the Assured Satisfaction Warranty

Within the 30 days from the date of purchase or the first 2/32nds tread wear as measured in the fastest wearing groove, you must return your tires to the authorized Pegasus LT/PCR tire dealer where you purchased your tires. You must present the original sales receipt and proof-of-purchase. Reason for dissatisfaction must be explained to the dealer (i.e., appearance, ride, handling, etc.) and noted on the adjustment claim form.

EXCLUSIONS

- A) All Pegasus LT/PCR tire warranties are limited to the original purchaser and the original vehicle on which they are mounted, and are not assignable to subsequent purchasers or vehicles.
- B) The warranties listed above are applicable only in the United States and Canada and any tire used or equipped on a vehicle registered or operated outside the United States and Canada are not covered by these warranties.
- C) The following is not covered by the warranties listed above:
- 1) Tire branded or marked “Non-Adjustable” (N/A) or “Blemished” (Blem), or previously adjusted.
 - 2) Failure, damage or irregular wear due to:
 - a) fire, accident or vandalism;
 - b) mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - c) misapplication of tire; or
 - d) alteration of the tire, addition of foreign material, transfers from one vehicle to another or any previous damages and/or repairs.
 - 3) Cost of mounting and balance service.
 - 4) Loss of time or use, inconvenience, or any incidental or consequential damages except as prohibited by law.
 - 5) Adjustment on out-of-balance or out-of-round tire is allowed only during the first 2/32” of the original tread as measured in the fastest wearing groove. A set of all four (4) tires from the same vehicle claimed for out-of-round will not be accepted.
- D) Any Pegasus LT/PCR tire produced five (5) years from date of manufacture as determined by the DOT/Serial number are not covered under the warranties listed above.

REPAIRS AND RETREADING: RATING CHANGES AND CAUTIONS

- A) Repaired, retreaded or altered Pegasus tire with “Speed Rating(s)” no longer retain their “Speed Rating”.
- B) If the aforementioned tire(s) is repairable, see the recommended repair procedures used by the tire dealer(s) for repairing tubeless passenger car radial tires as detailed and illustrated in the RMA puncture repair procedures.
- C) Repairs must be restricted to the tread area inside a half inch of the sidewall of the tire.
- D) Do not repair any punctures that are larger than 1/4 in diameter.

OWNER’S OBLIGATIONS

In order to be eligible for Pegasus LT/PCR tire Limited Warranty service, the dealer/owner must:

- A) At the time of purchase, the tires must be properly installed, correct air pressure set and the wheels balanced.
Every 6,000 miles the tires must be rotated, proper air pressures set and the wheel alignment checked.
- B) Any tire to be adjusted must be presented to an authorized Gladiator dealer.
- C) Present proof of purchase to the satisfaction of the dealer.
- D) Complete and sign a Pegasus Warranty Claim Form which is available at any authorized dealer.
- E) Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of Pegasus LT/PCR Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein. This warranty only applies the 48 contiguous continental United States, Alaska, Hawaii, District of Columbia and Canada.





PEGASUS
QUALITY SPEAKS FOR ITSELF®



SCAN TO VIEW ALL TIRE LINES

PEGASUS TIRES - 2026